

GENERAL GARDEN TRACTOR RULES

- Tech officials reserve the right to implement rule changes for safety and health at any time.
- All decisions by pull officials will be **FINAL**.
- Officials have the right to refuse participation from any participant at any time.
- Tractors Must have hood and grill.
- * Tractor may pull twice in each class. Must have a different driver for the second pull.
- * Driver may pull only once in each class.
- Hitch height no higher than 13" maximum.
- If weights or any part of tractor falls off during pull, the tractor will be disqualified.
- Driver is responsible for safe operation of their tractor.
- All weights must be secured to tractor.
- Any driver under the age of 16 must be supervised by an adult.
- All non-club members must sign a liability waiver(proof of insurance) or join the club for insurance coverage.
- Tractors with offensive wording or stickers on them will not be allowed to pull.
(Officials Decision)
- Tractors not to exceed 25 H.P. Motors.
- No parts of the tractor shall extend more than 3" past the sides of tires (including weights).
- Tractors must have stock OEM manufactured engine blocks only. No aftermarket blocks.
- No tire chains, dual wheels, or four wheel drives.
- Drivers must wear long pants and shoes. No shorts or sandals.
- Will County Threshermens Association is not responsible for any accidents.
- Drivers must have one hand on the steering wheel at all times.
- Drivers must remain in seat and have contact with seat at all times. No bouncing out of seat.
- Tech officials have the right to refuse tractor or puller from pulling at any time.
- The use of illegal drugs or alcohol will not be permitted at any event.
- No driving around (cruising) in pit or staging area.
- All hitches must be clear of any obstacles, such as weights, at all times.
- Hitch hole diameter, minimum of 1.5"
- All tractors must weigh before hooking to sled.

LAWN STOCK GARDEN TRACTORS

RULES

Lawn Stock Garden Tractors class is for kids age 6 – 16, who want to mow their yard, then load up their tractor and pull. The tractors must be **BONE STOCK**. You can't change or modify anything except by installing, bar or ribbed tires. Must have pulleys and brackets in place to prove tractor is being used for its manufacturer's intent.

- All tractors must have hood, and rear fenders in place for driver safety.
- Engine RPM must be governor controlled. Maximum rpm limit of 3650 RPM.
- All stock tractors must have factory issued parts for the listed horsepower not to exceed the maximum size of the class.
- Stock frames are required. No altering or axle movement will be allowed. Engine and front and rear axles must remain in stock location.
- Straight pipes and chrome air cleaners allowed.
- Must run factory appearing hood and grill, and rear-end. All tinwork, such as fenders, hood and grill, must match the brand of the frame. Engine swapping will not be allowed.
- Tractor can have mower deck in place, as long as drive belt is removed.
- Gas tanks and batteries must be in factory condition.
- Tractors are stock manufactured tractors. No home built.
- **Ribbed, Turf, and Bar Tires are allowed. No shaved, cut or professional pulling tires.**
- Hitch hole diameter, minimum of $\frac{3}{4}$ ".
- **Weight classes: up to 1200#**

STOCK GARDEN TRACTOR RULES

The Stock class is for those who want to dress things up a bit. Such as aluminum wheels, different hood, and fenders. But you cannot modify the motors. They must be Stock Motors, with Stock parts.

All stock tractors must have factory issued parts for the listed horsepower, not to exceed the maximum engine size of ~~26~~ HP. Interchanging parts for other than the listed horsepower above the maximum of the class will not be allowed.

Stock engines: (crank, rods, stroke, pistons, cam, head, and valves). Maximum overbore.030 is allowed. Porting and polishing is **NOT** allowed.

- Engine RPM must not exceed 4000 RPM.
- Engines must run on gasoline or diesel only; pump gas only, no additives. High octane fuels allowed. (Cam 2, etc.)
- Straight pipes and chrome air cleaners allowed.
- May strengthen drive train to prevent breakage. (rear-end, driveshaft, clutch, etc.)
- Aluminum wheels are allowed.
- **Bar tires** are allowed; but NO professionally made pulling tires. No shaved or cut tires.
- Shielding over belts, clutches, pulley's, and moving parts is required.
- Tractors must have wheelie bars or skid plates not over 5" off ground, and no closer than 5" behind rear tire, to prevent tractor from turning over backwards.
- Tractors must have hood, and rear fenders securely in place for driver safety.
- All tractors will have ignition shut-off switch conveniently located to the driver.
- Moving of front axle allowed up to 53", center front axle to center rear axle.
- Home built tractors are allowed as long as they follow the rules of the class.
- Tractors must have working fire extinguishers mounted securely on tractors.
- We would recommend tractors to have rear mounted dead-men throttles.
- Tractors must not exceed 8' in length, from center of rear axle to front of tractor.
- **Weight Classes:** 950#, up to 12Hp; 1050#, up to 25Hp; 1150# up to 25Hp

1200 #
SP4TCLASS
4X4
4 wheel Drive

ALTERED GARDEN TRACTOR RULES

- Garden tractor OEM manufactured block engines only.
- Aftermarket block engines not allowed.
- Porting and polishing is allowed.
- Steel flywheels are required.
- Must be shielding around all moving parts. (clutch, driveshaft, belts, pulleys, etc.)
- Tractors must have wheelie bars or skid plates not to exceed 5" behind tire, and 5 off the ground.
- Tractors must have working fire extinguishers mounted securely on tractors.
- Tractors must have dead-man throttles with return spring.
- Drivers must wear helmets approved for racing. No (football, baseball, bicycle, or toy)
- All tractors must have hood and rear fenders.
- May strengthen drive train to prevent breakage. (rear-end, driveshaft, clutch, etc.)
- May lengthen wheel base to 53" center front axle to center rear axle.
- No two engine tractors.
- Bar tires and professionally made pulling tires allowed.
- No starting carts allowed.
- Tractors must have working kill switch fastened to rear of tractor, connector must be fitted with a ring with a minimum of 1.5" inside diameter.
- Tractors must have easy access to ignition kill switch.
- Shielding over belts, clutches, pulley's, and moving parts is required.
- Tractor must not exceed 8' in length, from center of rear axle to front of tractor.
- **Weight Class: 1050#**

PROSTOCK GARDEN TRACTOR RULES

- All altered rules apply except:
- Prostock can go up to 50.5 cubic inch same as Superstock
- **Weight Class:** 1050#